

EMPRESS 15W

Recessed Fixed Downlight

The EMPRESS 15W Fixed downlight is an Architectural White Downlight, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with electricians.

EMPRESS 15W Fixed LED Down light adopts a high lumen COB LED, and PMMA diffuser with even light output. DALI dimmable version has shown great popularity with excellent dimming effect.

Verified by Techlume Australia on 27/03/2023









SPECIFICATIONS

Material Specifications

MaterialHigh Grade Aluminum + ReflectorDimensions110mm Face Dia x 65mm (H)

Cutout 90mm (Dia)

Colour Matt White (Black & Silver available for project

orders) IP65

Ingress ProtectionIP65Impact RatingIK06

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Dimmable, 23-40VDC 350mA

System Watts 15.0W

Input Voltage240V, 50/60HzOperating Temperature (Ta) -20° C to $+45^{\circ}$ C

Thermal Testing Compliant with IC Classification

Protection Voltage Overload, Temp Overload, Short Circuit

Connection Method Australian Plug & 1.2m Lead

Optic Specifications

 Light Source
 CREE 15W COB LED

 Delivered Lumens
 1,557lm (3000K)

 Delivered Lumens
 1,556lm (4000K)

 Efficacy
 Up to 104.1 lm/W

CRI > Ra 82

Beam Angle 60° (36° Available for Project Order)

 Reported L70 (Hours)
 > 60,000 Hrs

 Calculated L80 (Hours)
 > 60,000 Hrs


 Calculated L90 (Hours)
 > 56,000 Hrs

VARIATIONS

LC3574 EMPRESS 15W Fixed Downlight, White, 60°, Phase Dim, 3000K, 1,557lm LC3574B EMPRESS 15W Fixed Downlight, Black, 60°, Phase Dim, 3000K, 1,557lm LC3575 EMPRESS 15W Fixed Downlight, White, 60°, Phase Dim, 4000K, 1,556lm











LC3575B

EMPRESS 15W Fixed Downlight, Black, 60°, Phase Dim, 4000K, 1,556lm



