dynamic series

Efficient. Cutting Edge. Reliable



EMPRESS 8W

Recessed Fixed Downlight

The EMPRESS 8W Fixed downlight is available as phase dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with electricians.

EMPRESS 8W Fixed LED Down light adopts a high lumen COB LED, and PMMA diffuser with even light output.

Verified by Techlume Australia on 30/03/2023











SPECIFICATIONS

Material Specifications

MaterialHigh Grade Aluminum + ReflectorDimensions110mm Face Dia x 65mm (H)

Cutout 90mm (Dia

Colour Matt White (Black & Silver available for project

orders)

Ingress ProtectionIP65Impact RatingIK06

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Dimmable 23-40VDC 180mA

System Watts7.4W - 8.2WInput Voltage240V, 50/60HzOperating Temperature (Ta) $-20^{\circ}\text{C to} + 45^{\circ}\text{C}$

Thermal Testing Compliant with IC Classification

Protection Voltage Overload, Temp Overload, Short Circuit

Connection Method Australian Plug & 1.2m Lead

Optic Specifications

 Light Source
 CREE CXA1507 Series

 Delivered Lumens
 785lm - 891lm

 Efficacy
 Up to 110.3 lm/W

CRI Ra 83

Beam Angle 60° (36° Available for Project Order)

Reported L70 (Hours) >54,000 Hrs

VARIATIONS

LC3580EMPRESS 8W Fixed Downlight, White, 60°, Phase Dim, 3000K, 785ImLC3580-36EMPRESS 8W Fixed Downlight, White, 36°, Phase Dim, 3000K, 785ImLC3580BEMPRESS 8W Fixed Downlight, Black, 60°, Phase Dim, 3000K, 844ImLC3580SEMPRESS 8W Fixed Downlight, Silver, 60°, Phase Dim, 3000K, 785ImLC3581EMPRESS 8W Fixed Downlight, White, 60°, Phase Dim, 4000K, 891ImLC3581BEMPRESS 8W Fixed Downlight, Black, 60°, Phase Dim, 4000K, 891Im



