dynamic series

Efficient. Cutting Edge. Reliable



EMPRESS 8W

Recessed Gimbal Downlight

The EMPRESS 8W gimbal downlight is available as DALI dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with

EMPRESS 8W LED gimbal Downlight adopts a high lumen COB LED, and PMMA diffuser with even light output. DALI dimmable version has shown great popularity with excellent dimming effect.

Verified by Techlume Australia on 27/04/2023



electricians.









SPECIFICATIONS

Material Specifications

Material High Grade Aluminum + Reflector

Adjustment 30° gimbal

Dimensions 110mm Face Dia x 50mm (H)

Cutout 90mm (Dia)

Colour Matt White (Black & Silver available for project

orders)

Ingress ProtectionIP65Impact RatingIK06

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Dimmable 23-40VDC 180mA

System Watts 7.7W

Input Voltage240V, 50/60HzOperating Temperature (Ta) $-20^{\circ}\text{C to} + 45^{\circ}\text{C}$

Thermal Testing Compliant with IC Classification

Protection Voltage Overload, Temp Overload, Short Circuit

Connection Method Australian Plug & 1.2m Lead

Optic Specifications

 Light Source
 CREE CXA1507 Series

 Delivered Lumens
 785lm - 844lm

 Efficacy
 Up to 110.3 lm/W

CRI Ra 83

Beam Angle 60° (36° Available for Project Order)


 Calculated L70 (Hours)
 > 60,000 Hrs

 Calculated L80 (Hours)
 > 60,000 Hrs

 Calculated L90 (Hours)
 > 56,000 Hrs

VARIATIONS

LC3582 EMPRESS 8W Gimbal Downlight, White, 60°, Phase Dim, 3000K, 785lm
LC3582D EMPRESS 8W Gimbal Downlight, White, 60°, DALI, 3000K, 785lm
LC3582B EMPRESS 8W Gimbal Downlight, Black, 60°, Phase Dim, 3000K, 844lm





1300 827 284



LC3582S EMPRESS 8W Gimbal Downlight, Silver, 60°, Phase Dim, 3000K, 785lm
LC3583 EMPRESS 8W Gimbal Downlight, White, 60°, Phase Dim, 4000K, 891lm
LC3583-D EMPRESS 8W Gimbal Downlight, White, 60°, DALI, 4000K, 891lm
LC3583B EMPRESS 8W Gimbal Downlight, Black, 60°, Phase Dim, 4000K, 891lm
EMP08G-27
-36P

dynamic series
Efficient. Cutting Edge. Reliable

