

EXODUS AQUA65 4W

Weatherproof IP65 Exit Light

Synthium LED Surface Mounted Weatherproof IP65 Exit Light c/w Synthium Battery. The AQUA65 is a sturdy wall-mounted LED Exit Light that is designed to withstand external environments and harsh weather conditions. it produces excellent illumination with a long-lasting battery for years of dependable exit lighting.

It has a robust, water-tight polycarbonate enclosure, providing excellent protection against water and dust. Suitable for Car Parks, exposed stairwells, indoor swimming centers, construction zones, train stations, and cool rooms. C0-D6.3, C90-E3.2

Using a remote box for the battery allows an operating temperature of -30°C to +40°C.

Viewing distance 24m.



SPECIFICATIONS

Material Specifications

Material	Flame-Retardant Polycarbonate
Mounting	Surface Mounted - Wall or Ceiling
Dimensions	415mm(L) x 70mm(W) x 230mm(H)
Weight	2.5 Kg
Ingress Protection	IP65
Impact Rating	IK10
Warranty	5 Year Replacement

Electrical Specifications

Input Voltage	230V, 50Hz
Connection Method	Large Terminal Block, 20mm ² Cable Entry
Mode of Operation	Maintained
Battery & Charger System	Lithium Battery w. Intelligent 3-stage charger and battery management
Emergency Duration	> 120 minutes
Indicators	Batter Charger Green LED
Operating Temperature (Ta)	1°C - 40°C

Optic Specifications

LED Wattage	4W (Standby)
Light Source	High output LED Strip
AS2293 Classification	C0-D6.3, C90 D3.2

SPACING TABLE		MOUNTING HEIGHT (m)			
NATA Classification		2.1	2.4	2.7	3.0*
EXS-AQUA65	C0 - D6.3	8.6	8.8	9.0	9.1
	C90 - D3.2	6.0	6.2	6.4	6.6

* Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2005

VARIATIONS

EXS-AQUA65	AQUA65 4W IP65 Exit - 24m, maint., White
EXS-AQUA65-B	AQUA65 4W IP65 Exit - 24m, maint., Black
EXS-AQUA65-RB	AQUA65 4W IP65 Exit - 24m, maint. Remote Box for Freezers

**EXS-
AQUA65-RF**

AQUA65 4W IP65 Exit c/w Wireless Monitoring - 24m, maint.

**EXS-
AQUA65-B-
RF**

AQUA65 4W IP65 Exit c/w Wireless Monitoring - 24m, maint., Black