

# EXODUS BOXTER-W 2W

## Wall Wide-Base Exit Light

Synthium LED Surface Mounted Wide Base Wall Exit Light c/w Synthium Battery. This LED Exit light is presented in a traditional rectangular profile with a large 'PushConnect' mounting base to give installers the ultimate in simplicity, flexibility and versatility.

The wide base allows installers to easily run conduit, hide access cable and conceal existing defects on a previous installation, thus reducing unforeseen and undesirable site-related challenges.

Comes with all variations of the Running Man pictogram. C0-D8, C90-D5



### SPECIFICATIONS

#### Material Specifications

|                           |                               |
|---------------------------|-------------------------------|
| <b>Material</b>           | Flame-Retardant Polycarbonate |
| <b>Mounting</b>           | Surface Mounted - Wall        |
| <b>Dimensions</b>         | 355mm(L) x 65mm(W) x 210mm(H) |
| <b>Weight</b>             | 1.5Kg                         |
| <b>Ingress Protection</b> | IP20                          |
| <b>Warranty</b>           | 5 Year Replacement            |

#### Electrical Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Input Voltage</b>                | 240V; 50Hz  |
| <b>Mode of Operation</b>            | Maintained  |
| <b>Battery &amp; Charger System</b> | Lithium Battery w. Intelligent 3-stage charger and battery management |
| <b>Operating Temperature (Ta)</b>   | 1°C - 40°C  |
| <b>Protection</b>                   | overcharge, low voltage disconnect, overcurrent, short circuit        |
| <b>Connection Method</b>            | Large Terminal Block, 20mm <sup>2</sup> Cable Entry                   |
| <b>Emergency Duration</b>           | >120 Minutes  |
| <b>Testing Facility</b>             | Manual Test Switch  |
| <b>Indicators</b>                   | Battery Charge Green LED  |

#### Optic Specifications

|                                |                       |
|--------------------------------|-----------------------|
| <b>Light Source</b>            | High output LED Strip |
| <b>LED Wattage</b>             | 2W (Standby)          |
| <b>AS2293 Classification</b>   | C0-D8, C90-D5         |
| <b>Rated Lifetime (L70B20)</b> | 50,000 Hrs            |



### VARIATIONS

**EXS-BOXW** BOXSTER-W 2W Wall Wide Base Exit - 24m, maint.