

EXODUS JUMBO 6W

Surface Mount 48m Exit Light

The EXODUS JUMBO 6W Surface Mount 48m Exit Light provides double the viewing distance compared to conventional Exit Lights and comes complete with a set of directional decals for single or double sided configurations. It comes in a robust steel chassis and can be suspended, wall or ceiling mounted to suit large indoor spaces such as stadiums, warehouses, car parks, public buildings and train stations. C0-D6.3, C90-E3.2



SPECIFICATIONS

Material Specifications

| | |
|---------------------------|-----------------------------------|
| Material | Flame-Retardant Polycarbonate |
| Mounting | Surface Mounted - Wall or Ceiling |
| Dimensions | 630mm(L) x 100mm(W) x 365mm(H) |
| Weight | 5.0Kg |
| Ingress Protection | IP20 |
| Warranty | 5 Year Replacement |


Electrical Specifications

| | |
|-------------------------------------|---|
| Input Voltage | 240V, 50Hz |
| Connection Method | Large Terminal Block, 20mm ² Cable Entry |
| Mode of Operation | Maintained |
| Battery & Charger System | Lithium Battery w. Intelligent 3-stage charger and battery management |
| Emergency Duration | > 120 minutes |
| Indicators | Batter Charger Green LED |
| Operating Temperature (Ta) | 1°C - 40°C |

Optic Specifications

| | |
|------------------------------|-----------------------|
| LED Wattage | (6W Standby) |
| Light Source | High output LED Strip |
| AS2293 Classification | C0-D6.3, C90-E3.2 |

Dimensions



VARIATIONS

| | |
|---------------------|---|
| EXS-JUMBO | EXODUS JUMBO 6W Surface Mount Exit - 48m, maintained, White |
| EXS-JUMBO-RF | EXODUS JUMBO 6W Surface Mount Exit - 48m, maintained, c/w Wireless RF Monitoring, White |