

GRANGE 60W

Architectural Streetlight 4000K

Classic Series

Proven. Quality. Customisable

The GRANGE 60W Roadway Lighting Series is powered by the Crystal OpticLED platform, and features innovative thermal management design, offering exceptional performance and value. This versatile luminaire can be tailored to the unique specifications of each project. Tool Free Opening Clip, allowing for Top Opening Easy Maintenance. The GRANGE Streetlight Series is fitted with knife switch safety feature to cut off power supply when the device is open.

NOTE: side mount only, cannot be post top mounted.

Verified by Techlume Australia on 24/05/2023



SPECIFICATIONS

Material Specifications

Housing	High Pressure Die-Cast Aluminium Alloy, Clear Tempered Glass
Finish	Polyester Powder Coat, Signal Black
Dimensions	350mm(L) x 230mm(W) x 85mm(H)
Spigot Size	60mm
Ingress Protection	IP66
Impact Rating	IK09
Weight	5.0kg
Mounting Height	4m - 6m
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Integrated Meanwell Driver
Input Voltage	240VAC
Operating Temperature (Ta)	-25° to + 50°C

Optic Specifications

Light Source	LED 12 x SMD
Efficacy	> 144lm/W
CRI	72Ra
Reported L70 (Hours)	> 54,000 Hrs
Calculated L70 (Hours)	79,000 Hrs
Calculated L90 (Hours)	43,500 Hrs

VARIATIONS

LC2121-T3	GRANGE 60W Architectural Streetlight, Signal Black, T3, 4000K, 9,760lm
LC2121-T4	GRANGE 60W Architectural Streetlight, Signal Black, T4, 4000K, 9,064lm