

HAWKE 1000W

Asymmetric Sports Light

Classic Series

Proven. Quality. Customisable

The HAWKE 1000W Floodlights are designed for flexibility in high output situations. Designed with different beam angles for use in sports grounds and arenas. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, for less wind force, and an improved bracket design.



IP66



SPECIFICATIONS

Material Specifications

Material	Die-Cast Aluminium Housing
Finish	AkzoNobel Powder Coat
Colour	Dusty Grey (RAL7037)
Dimensions	588mm (W) x 652mm (H) x 351mm (D)
Windage	0.08m ² at 0° tilt
Ingress Protection	IP66
Impact Rating	IK10
Weight	24.4kg (including drivers)
Weight	18.2kg (without drivers)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	1pcs Inventronics Driver NES-1K8T210BC
Input Voltage	240V (4.2 amps)
Max Distance From Power Supply	200m
Connection Method	Drivers can be remoted mounted

Optic Specifications

Light Source	Seoul SMD 3535 LED
CRI	> 70 Ra
Delivered Lumens	135,200-140,200lm
Calculated L70 (Hours)	315,000 Hrs
Calculated L80 (Hours)	192,000 Hrs
Calculated L90 (Hours)	83,000 Hrs

VARIATIONS

LC7883-40 x15	HAWKE 1000W Floodlight, Grey, 40x15°, Non-Dim, 3000K
LC7884-40 x15	HAWKE 1000W Floodlight, Grey, 40x15°, Non-Dim, 4000K
LC7883-100x17	HAWKE 1000W Floodlight, Grey, 100x17°, Non-Dim, 3000K
LC7884-100x17	HAWKE 1000W Floodlight, Grey, 100x17°, Non-Dim, 4000K

