

# HAWKE 1000W

## Asymmetric Sports Light

**Classic Series**

Proven. Quality. Customisable

The HAWKE 1000W Floodlights are designed for flexibility in high output situations. Designed with different beam angles for use in sports grounds and arenas. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, for less wind force, and an improved bracket design.



**IP66**



### SPECIFICATIONS

#### Material Specifications

|                           |                                   |
|---------------------------|-----------------------------------|
| <b>Material</b>           | Die-Cast Aluminium Housing        |
| <b>Finish</b>             | AkzoNobel Powder Coat             |
| <b>Colour</b>             | Dusty Grey (RAL7037)              |
| <b>Dimensions</b>         | 588mm (W) x 652mm (H) x 351mm (D) |
| <b>Windage</b>            | 0.08m <sup>2</sup> at 0° tilt     |
| <b>Ingress Protection</b> | IP66                              |
| <b>Impact Rating</b>      | IK10                              |
| <b>Weight</b>             | 24.4kg (including drivers)        |
| <b>Weight</b>             | 18.2kg (without drivers)          |
| <b>Warranty</b>           | 5 Year Replacement                |

#### Electrical Specifications

|                                       |  |
|---------------------------------------|--|
| <b>Power Supply</b>                   | 1pcs Inventronics Driver NES-1K8T210BC |
| <b>Input Voltage</b>                  | 240V (4.2 amps)                        |
| <b>Max Distance From Power Supply</b> | 200m                                   |
| <b>Connection Method</b>              | Drivers can be remoted mounted         |

#### Optic Specifications

|                               |                    |
|-------------------------------|--------------------|
| <b>Light Source</b>           | Seoul SMD 3535 LED |
| <b>CRI</b>                    | > 70 Ra            |
| <b>Delivered Lumens</b>       | 135,200-140,200lm  |
| <b>Calculated L70 (Hours)</b> | 315,000 Hrs        |
| <b>Calculated L80 (Hours)</b> | 192,000 Hrs        |
| <b>Calculated L90 (Hours)</b> | 83,000 Hrs         |

### VARIATIONS

|                      |   |
|----------------------|---|
| <b>LC7883-40 x15</b> | HAWKE 1000W Floodlight, Grey, 40x15°, Non-Dim, 3000K  |
| <b>LC7884-40 x15</b> | HAWKE 1000W Floodlight, Grey, 40x15°, Non-Dim, 4000K  |
| <b>LC7883-100x17</b> | HAWKE 1000W Floodlight, Grey, 100x17°, Non-Dim, 3000K |
| <b>LC7884-100x17</b> | HAWKE 1000W Floodlight, Grey, 100x17°, Non-Dim, 4000K |

