

HAWKE 1500W

Asymmetric Sports Light

The HAWKE Floodlights are designed for flexibility in high output situations. The HAWKE 1500W Asymmetric Sports Light is suitable for mounting heights of up to 30 metres. Designed with different beam angles for use in sports grounds and arenas. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, for less wind force, and an improved bracket design.



IP66



SPECIFICATIONS

Material Specifications

Material Die-Cast Aluminium Housing **Finish** AkzoNobel Powder Coat Colour Dusty Grey (RAL7037)

Dimensions 568mm (W) x 953mm (H) x 271mm (D)

0.08m² at 0° tilt Windage

Ingress Protection IP66 **Impact Rating** IK10

Weight 35.8kg (including drivers) Weight 28.8kg (without drivers) 5 Year Replacement Warranty

Electrical Specifications

1pcs Inventronics Driver NES-1K8T210BC **Power Supply**

240V (5 amps) Input Voltage

Max Distance From Power Supply

Connection Method Drivers can be remoted mounted

Optic Specifications

Light Source Seoul 3535 LED **Delivered Lumens** 212,200 - 231,000lm Calculated L70 (Hours) 315,000 Hrs

Calculated L80 (Hours) 192,000 Hrs Calculated L90 (Hours) 83,000 Hrs

VARIATIONS

LC7801-40 HAWKE 1500W Floodlight, Grey, 40x15°, Non-Dim, 4000K x15

LC7801-100 HAWKE 1500W Floodlight, Grey, 100x17°, Non-Dim, 4000K

x17

LC7801V-10 HAWKE 1500W Floodlight, Grey, 100x60°, Non-Dim, 4000K 0x60

LC7801-130 HAWKE 1500W Floodlight, Grey, 130x25°, Non-Dim, 4000K

HAWKE 1500W Floodlight, 240V, w. Glare Shield, Grey, Combination, LC7801-CA-


Non-Dim, 4000K, 191,834lm

LC7801V-HAWKE 1500W Floodlight, 415V, w. Glare Shield, Grey, Combination, CA-GS


Non-Dim, 4000K, 191,834lm













x25



Classic Series Proven. Quality. Customisable

