

# **HAWKE 1500W**

# Asymmetric Sports Light

The HAWKE Floodlights are designed for flexibility in high output situations. The HAWKE 1500W Asymmetric Sports Light is suitable for mounting heights of up to 30 metres. Designed with different beam angles for use in sports grounds and arenas. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, for less wind force, and an improved bracket design.





## SPECIFICATIONS

#### **Material Specifications**

MaterialDie-Cast Aluminium HousingFinishAkzoNobel Powder CoatColourDusty Grey (RAL7037)

**Dimensions** 568mm (W) x 953mm (H) x 271mm (D)

Windage 0.08m<sup>2</sup> at 0° tilt

Ingress ProtectionIP66Impact RatingIK10

Weight 35.8kg (including drivers)
Weight 28.8kg (without drivers)
Warranty 5 Year Replacement

## **Electrical Specifications**

**Power Supply** 1pcs Inventronics Driver NES-1K8T210BC

**Input Voltage** 240V (5 amps)

**Max Distance From Power Supply** 200m

**Connection Method** Drivers can be remoted mounted

### **Optic Specifications**

 Light Source
 Seoul 3535 LED

 Delivered Lumens
 212,200 - 231,000 lm

 Calculated L70 (Hours)
 315,000 Hrs

 Calculated L80 (Hours)
 192,000 Hrs

 Calculated L70 (Hours)
 315,000 Hrs

 Calculated L80 (Hours)
 192,000 Hrs

 Calculated L90 (Hours)
 83,000 Hrs

#### VARIATIONS

**LC7801-40** HAWKE 1500W Floodlight, Grey, 40x15°, Non-Dim, 4000K **x15** 

**LC7801-100** HAWKE 1500W Floodlight, Grey, 100x17°, Non-Dim, 4000K

**x17 LC7801-100**HAWKE 1500W Floodlight, Grey, 100x60°, Non-Dim, 4000K

**x60 LC7801-130**HAWKE 1500W Floodlight, Grey, 130x25°, Non-Dim, 4000K

x25


**LC7801-CA-** HAWKE 1500W Floodlight, 240V, w. Glare Shield, Grey, Combination, Non-Dim, 4000K, 191,834lm

**LC7801V-** HAWKE 1500W Floodlight, 415V, w. Glare Shield, Grey, Combination,


**CA-GS** Non-Dim, 4000K, 191,834lm















**Classic Series** Proven. Quality. Customisable

