

HAWKE 500W

Asymmetric Sports Floodlight

The HAWKE 500W Floodlight is designed with different beam angles for use in sports grounds and arenas. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, with less wind force, and an improved bracket design.



IP66



SPECIFICATIONS

Material Specifications

MaterialDie-Cast Aluminium HousingFinishAkzoNobel Powder CoatColourDusty Grey (RAL7037)

Ingress ProtectionIP66Impact RatingIK10

Dimensions 310mm (W) x 500mm (H) x 275mm (D)

 Dimensions
 Bracket: 390mm(W)

 Windage
 0.096m² at 20° tilt

 Weight
 17.4Kg (including drivers)

 Weight
 11.0Kg (without drivers)

 Warranty
 5 Year Replacement

Electrical Specifications

Power Supply Inventronics Input Voltage 220 - 415V

Connection Method Driver can be remote mounted

Max Distance From Power Supply 50

Protection Thermal Control Unit, and Inrush Current Limiter,

20KV Surge Protection.

Optic Specifications

Light Source Seoul LED CRI > 70Ra

 Calculated L70 (Hours)
 341,000 Hrs (L70B50)

 Calculated L80 (Hours)
 215,000 Hrs (L80B50)


 Calculated L90 (Hours)
 104,000 Hrs (L90B50)


VARIATIONS


LC7825-40 HAWKE 500W Floodlight, Grey, 40x15°, Non-Dim, 5700K, 73,000lm x15 LC7825-60 HAWKE 500W Floodlight, Grey, 60x15°, Non-Dim, 5700K, 73,000lm x15 LC7823-10 HAWKE 500W Floodlight, Grey, 100x17°, Non-Dim, 3000K, 73,000lm 0x17 LC7824-10 HAWKE 500W Floodlight, Grey, 100x17°, Non-Dim, 4000K, 73,000lm 0x17 LC7824-10 HAWKE 500W Floodlight, Grey, 100x60°, Non-Dim, 4000K, 73,000lm 0x60 LC7824D-1 HAWKE 500W Floodlight, Grey, $100x17^{\circ}$, DALI-2, 4000K, 73,000lm













1300 827 284



00x17 LC7824D-1 00x60

HAWKE 500W Floodlight, Grey, 100x60°, DALI-2, 4000K, 73,000lm

Classic Series
Proven. Quality. Customisable

