

DEX 60W

Streetlight PE Cell

dynamic series


Efficient. Cutting Edge. Reliable

DEX 60W LED Carpark and Street Light is an effective energy replacement of metal halide equivalents. Streetlights with PE Cells are available from 40-watt up to 120-watts. This fixture can be mounted to building or light poles.

The Dex Streetlight Range is designed for exterior applications where design and style matters. Suited for carparks, boardwalks and common thoroughfares. Designed specifically for outdoor parking, Energy-efficient, low-glare LED street lights provide high-quality car park illumination for optimal vision while avoiding light spill.



IP65



SPECIFICATIONS

Material Specifications

Material	Die-Cast High Grade Aluminium
Colour	Corrosion Resistant Powder Coat, Black
Dimensions	500mm (L) x 215mm (W) x 100mm (H)
Spigot Size	53mm (Dia)
Impact Rating	IK09
Ingress Protection	IP65
Weight	2.4kg
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Integral Sosen Driver, Non-Dimmable
Input Voltage	240V
Connection Method	Hard Wiring Required
Benefits	In-built PE Cell
Operating Temperature (Ta)	-25°C to +45°C

Optic Specifications

Light Source	1pc 60W Epistar COB
Delivered Lumens	7670lm
Beam Angle	150°
CRI	80Ra
Correlated Colour Temperature	5700K
Rated Lifetime (L70B20)	40,000 Hrs

VARIATIONS

LC6509	DEX 60W LED Streetlight w. PE Cell, Black, Non-Dim, 5700K
---------------	---