

INVICTUS 750W

Sports Floodlight


Classic Series

Proven. Quality. Customisable

The INVICTUS 750W Floodlight is a striking, low-profile design and advanced in-built thermal management. The latest generation floodlight is a highly reliable fitting that requires very low maintenance. Producing a vivid white light that renders colours as they are meant to be seen, this revolutionary fitting has helped redefine high-output illumination as we know it.

Using a versatile 240V-415V Integrated driver, it has an inbuilt thermostat, which will dim the light to 25% if the lights are overheating. When installed correctly, these lights are guaranteed with a 10-year warranty.

Sail Area @ 40 degrees = 0.250.



IP66



SPECIFICATIONS

Material Specifications

Material	Aluminium Body
Dimensions	1175mm (L) x 396mm (H) x 95mm (D) - these are with integrated drivers
Dimensions	839mm(L) x 396mm (H) x 95mm (D) - these are with remote mounted drivers
Options	Driver Mounting - Integrated or Remote
Ingress Protection	IP66
Impact Rating	IK09
Weight	19kg exc. drivers. 32kg inc. drivers
Warranty	10 Year Replacement*

Electrical Specifications

Input Voltage	200 - 415VAC, 50/60 Hz
Operating Temperature (Ta)	-40°C - +50°C

Optic Specifications

Light Source	Osram 3030 LED
Efficacy	150lm/W
Optics	Medium Flood Asymmetric/ 120° Symmetrical
Efficacy	150lm/W
CRI	> 70Ra
Calculated L70 (Hours)	> 100,000 Hrs

VARIATIONS

LC7640	INVICTUS 750W Floodlight, Black, Medium Flood Asymmetric, DALI, 5000K, 105,000lm
---------------	--

