

KALO 13W

Commercial Downlight 100mm

The **KALO** Super Comfort Deep Recessed 13W Commercial Downlight 100mm is used in commercial applications where style and class is important. At IP54 Rated, it can be used in schools, hospitals, corridors and wet areas. With a matt silver reflector and diffused lens the <u>KALO series</u> offers excellent optical control along with architectural interest.









SPECIFICATIONS

Material Specifications

MaterialHigh Grade AluminiumFinishSmooth Powder CoatDimensions110mm Dia x 79mm (H)

 Cutout
 100mm (Dia)

 Ingress Protection
 IP54

Warranty 5 Year Replacement

Electrical Specifications

Power Supply15W Actec Phase Dim DriverOptionsDALI Available, 30° Beam AngleConnection MethodAustralian 2-Pin Plug and 1.0m Lead

Input Voltage 240V

Optic Specifications

Light Source Citizen COB LED

 Delivered Lumens
 1300 lm

 CRI
 83 Ra

 Beam Angle
 50°

 Colour Deviation
 SDCM ≤ 3

 Reported L70 (Hours)
 > 54,000 Hrs

 Calculated L70 (Hours)
 115,000 Hrs

VARIATIONS

LC5420 KALO 13W Commercial Downlight, White, 50°, Phase Dim, 3000K,

1287lm

LC5420B KALO 13W Commercial Downlight, Black, 50°, Phase Dim, 3000K,

1287lm

LC5421 KALO 13W Commercial Downlight, White, 50°, Phase Dim, 4000K,

1369lm


LC5421B KALO 13W Commercial Downlight, Black, 50°, Phase Dim, 4000K,

1369lm





79



Ø110



Product design and technical data may be subject to change without prior notice.

Generated 28th Dec 2024 - © Decrolux