

1300 827 284 www.decrolux.com.au

## **KALO 18W** Commercial Downlight 150mm

The KALO 18W Deep Recessed Commercial Downlight is used in commercial applications where style and class are important. At IP54 Rated, it can be used in schools, hospitals, corridors and wet areas. With a matt silver reflector and diffused lens, the KALO series offers excellent optical control along with visual interest.



### SPECIFICATIONS

#### **Material Specifications**

Material Finish Dimensions Cutout **Ingress Protection** Warranty

High Grade Aluminium Smooth Powder Coat 160mm Dia x 100mm (H) 150mm (Dia) IP54 5 Year Replacement

#### **Electrical Specifications**

**Power Supply** 

Input Voltage

Options


ACTEC 21W Phase-Dimmable Driver DALI Available Australian 2-Pin Plug and 1.0m Lead **Connection Method** 240V

#### **Optic Specifications**

Light Source **Delivered Lumens** UGR CRI Calculated L90 (Hours) **Beam Angle Colour Deviation** 

Citizen COB LED 2000lm <19 90 >52,000 Hrs 60° SDCM ≤ 3

# 00





#### VARIATIONS

LC5430	KALO 18W Commercial Downlight, White, 60°, Phase Dim, 3000K, 2027lm
LC5430B	KALO 18W Commercial Downlight, Black, 60°, Phase Dim, 3000K, 2027Im
LC5431	KALO 18W Commercial Downlight, White, 60°, Phase Dim, 4000K, 2087lm
LC5431B	KALO 18W Commercial Downlight, Black, 60°, Phase Dim, 4000K, 2087lm

**Classic Series** Proven. Quality. Customisable



