

KALO 25W

Commercial Downlight 150mm

The KALO 25W Commercial Downlight is used in commercial applications where style and class are important. Boasting a low profile for the output, this IP54 Rated Downlight is used in schools, hospitals, corridors and wet areas. With a matt silver reflector and diffused lens the KALO series offers excellent optical control along with visual interest.









SPECIFICATIONS

Material Specifications

Material High Grade Aluminium Finish Smooth Powder Coat 160mm Dia x 100mm (H) **Dimensions**

Cutout 150mm (Dia) IP54 **Ingress Protection**

Warranty 5 Year Replacement

Electrical Specifications

Power Supply 28W Actec Phase Dim Driver

Options DALI Available

Connection Method Australian 2-Pin Plug and 1.0m Lead

Input Voltage 240V

Optic Specifications

Light Source Citizen COB LED


Delivered Lumens 2700lm **UGR** <19 CRI 83Ra **Beam Angle** 60° SDCM ≤ 3 **Colour Deviation** Reported L70 (Hours) > 54.000 Hrs Calculated L70 (Hours) 115,000 Hrs

VARIATIONS

LC5440 KALO 25W Commercial Downlight, White, 60°, Phase Dim, 3000K LC5440B KALO 25W Commercial Downlight, Black, 60°, Phase Dim, 3000K LC5441 KALO 25W Commercial Downlight, White, 60°, Phase Dim, 4000K LC5441B KALO 25W Commercial Downlight, Black, 60°, Phase Dim, 4000K LC5451 KALO 25W Commercial Downlight, White, 60°, Phase Dim, 4000K LC5451D KALO 25W Commercial Downlight, White, 60°, DALI, 4000K

Classic Series Proven. Quality. Customisable





Ø160

