

# KALO 38W

## Commercial Downlight 200mm

### Classic Series

Proven. Quality. Customisable

The KALO 38W Commercial Downlight is used in commercial applications. Installation areas include foyers, lobbies, corridors and toilets and schools.

The KALO commercial downlight range offers a high performance lighting solution, delivering up to 60% energy savings as a twin compact fluorescent (CFL) or metal halide light replacement.



**IP54**



### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	Aluminium
<b>Finish</b>	Textured Powder Coat - Black or White
<b>Accessories</b>	Black, White or Matt Silver Reflector
<b>Dimensions</b>	218mm Face Dia x 132mm (H)
<b>Cutout</b>	200mm (Dia)
<b>Ingress Protection</b>	IP54
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>Power Supply</b>	Tridonic 42W Non-Dimmable driver
<b>Options</b>	DALI, 1-10V, Phase-Dim Available
<b>Connection Method</b>	Australian 2-Pin Plug & 1.0m Lead
<b>Input Voltage</b>	240V

#### Optic Specifications

<b>Light Source</b>	Citizen COB LED
<b>Delivered Lumens</b>	3800 - 4000lm
<b>UGR</b>	<19
<b>CRI</b>	83Ra
<b>Beam Angle</b>	60° (18° & 30° Optional)
<b>Colour Deviation</b>	SDCM ≤ 3
<b>Reported L70 (Hours)</b>	> 54,000 Hrs
<b>Calculated L70 (Hours)</b>	115,000 Hrs

### VARIATIONS

<b>LC5460</b>	KALO 38W Commercial Downlight, White, Phase Dim, 3000K, 3882lm
<b>LC5460B</b>	KALO 38W Commercial Downlight, Black, Phase Dim, 3000K, 3882lm
<b>LC5461</b>	KALO 38W Commercial Downlight, White, Phase Dim, 4000K, 4023lm
<b>LC5461D</b>	KALO 38W Commercial Downlight, White, DALI, 4000K, 4023lm
<b>LC5461B</b>	KALO 38W Commercial Downlight, Black, Phase Dim, 4000K, 4023lm
<b>LC5460D</b>	KALO 38W Commercial Downlight, White, DALI, 3000K, 3882lm

