

# KARGO 15W

## LED Recessed Downlight 120mm


dynamic series

Efficient. Cutting Edge. Reliable

The KARGO 15W downlight is phase dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with electricians.

KARGO 15W LED Downlight adopts a high lumen SMD LED, and PMMA diffuser with even light output.

Verified by Techlume Australia on 28/07/2023



IP54



### SPECIFICATIONS

#### Material Specifications

Material	High Grade Aluminium + PC Reflector
Colour	Matt White (RAL9016)
Dimensions	145mm Face Dia x 45mm (H)
Cutout	120mm (Dia)
Ingress Protection	IP54
Impact Rating	IK06
Warranty	5 Year Replacement

#### Electrical Specifications

Power Supply	Remote Driver 300mA, Phase Dim
System Watts	14.1W - 15.3W
Thermal Testing	Compliant with IC-4 Classification
Operating Temperature (Ta)	-20°C to +45°C
Input Voltage	240V, 50/60Hz
Connection Method	Australian 2-Pin Plug & 0.6m Lead

#### Optic Specifications

Light Source	15W SMD 2835 LED
Delivered Lumens	1,286lm (3000K)
Delivered Lumens	1,540lm (4000K)
Delivered Lumens	1,504lm (5500K)
Efficacy	Up to 109.1lm/W
CRI	Ra >82
Calculated L90 (Hours)	> 56,000 Hrs

### VARIATIONS

LC3621	KARGO 15W Downlight, White, 100°, Phase Dim, Tri-Colour
LC3621B	KARGO 15W Downlight, Black, 100°, Phase Dim, Tri-Colour
LC3621D	KARGO 15W Downlight, White, 100°, DALI, Tri-Colour