

# KARGO 25W

## LED Recessed Downlight 160mm Cutout


dynamic series

Efficient. Cutting Edge. Reliable

The KARGO 25W downlight is phase dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with electricians.

KARGO 25W LED Downlight adopts a high lumen SMD LED, and PMMA diffuser with even light output.

Verified by Techlume Australia on 27/07/2023



IP54



### SPECIFICATIONS

#### Material Specifications


Material	High Grade Aluminium + PC Reflector
Colour	Matt White (RAL9016)
Dimensions	190mm Face Dia x 45mm (H)
Cutout	160mm (Dia)
Ingress Protection	IP54
Impact Rating	IK06
Warranty	5 Year Replacement

#### Electrical Specifications

Power Supply	Remote Driver 300mA, Phase Dim
System Watts	23.1W - 24.4W
Thermal Testing	Compliant with IC-4 Classification
Operating Temperature (Ta)	-20°C to +45°C
Input Voltage	240V, 50/60Hz
Connection Method	Australian 2-Pin Plug & 0.6m Lead

#### Optic Specifications

Light Source	25W SMD 2835 LED
Delivered Lumens	2243lm (3000K)
Delivered Lumens	2533lm (4000K)
Delivered Lumens	2435lm (5500K)
Efficacy	Up to 109.9lm/W
CRI	>82Ra
Calculated L90 (Hours)	> 56,000 Hrs



### VARIATIONS

LC3641	KARGO 25W Downlight, White, 100°, Phase Dim, Tri Colour
LC3641B	KARGO 25W Downlight, Black, 100°, Phase Dim, Tri Colour
LC3641D	KARGO 25W Downlight, White, 100°, DALI, Tri Colour
LC3641RD	KARGO 25W Downlight, CRI90, White, 100°, DALI, Tri Colour