

KINGSTON 300W

Architectural Streetlight

The KINGSTON 300W Roadway Lighting Series is powered by the Crystal OpticLED platform, and features innovative thermal management design, offering exceptional performance and value. This versatile luminaire can be tailored to the unique specifications of each project. Tool Free Opening Clip, allowing for Top Opening Easy Maintenance. The KINGSTON Streetlight Series is fitted with knife switch safety feature to cut off power supply when the device is open.







SPECIFICATIONS

Material Specifications

Housing High Pressure Die-Cast Aluminium Alloy, Clear

Tempered Glass

Finish Polyester Powder Coat, Signal Black **Dimensions** 793mm(L) x 300mm(W) x 109mm(H)

Spigot Size 60mm **Ingress Protection** IP66 **Impact Rating** IK10 Weight 9.2kg **Mounting Height** 10m - 12m **Adjustment** Up to 15° tilt Warranty 5 Year Replacement

Electrical Specifications

Power Supply 320W Integrated Inventronics Driver

Input Voltage 240VAC, 50/60Hz

Dimming System/ PE Cell/ NEMA Socket **Options**

Operating Temperature (Ta) -20°C to + 55°C

Optic Specifications

Light Source Phillips LED SMD 5050 x 192

Delivered Lumens 42,600lm - 46,257lm

79Ra

Calculated L70 (Hours) >125,000 Hrs Calculated L80 (Hours) >80,000 Hrs Calculated L90 (Hours) >38,000 Hrs

VARIATIONS

LC6180-T2 KINGSTON 300W Streetlight, Signal Black, T2, 4000K, 42,600lm

LC6180D-**T2**

KINGSTON 300W Streetlight, Signal Black, T2, DALI, 4000K, 42,600lm

LC6180-T3

KINGSTON 300W Streetlight, Signal Black, T3, 4000K, 43,107lm

LC6180D-**T3**

KINGSTON 300W Streetlight, Signal Black, T3, DALI, 4000K, 43,107lm

LC6180D-

LC6180-T4 KINGSTON 300W Streetlight, Signal Black, T4, 4000K, 46,257lm KINGSTON 300W Streetlight, Signal Black, T4, DALI, 4000K, 46,257lm

Classic Series Proven. Quality. Customisable





