

KINGSTON 75W

Architectural Streetlight

The KINGSTON 75W Roadway Lighting Series is powered by the Crystal OpticLED platform, and features an innovative thermal management design, offering exceptional performance and value. This versatile luminaire can be tailored to the unique specifications of each project. Tool-Free Opening Clip, allowing for Top Opening Easy Maintenance. The KINGSTON Streetlight Series is fitted with a knife switch safety feature to cut off the power supply when the device is open.

Verified by Techlume Australia on 11/04/2023









SPECIFICATIONS

Material Specifications

Housing High Pressure Die-Cast Aluminium Alloy, Clear

Tempered Glass

Finish Polyester Powder Coat, Signal Black **Dimensions** 568mm(L) x 200mm(W) x 109mm(H)

60mm **Spigot Size Ingress Protection** IP66 **Impact Rating** IK10 Weight 5.7kg **Mounting Height** 6m - 8m

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Integrated Inventronics Driver

System Watts 76.6W - 76.9W Input Voltage 240VAC, 50/60Hz

Dimming System/ PE Cell/ NEMA Socket **Options**

Operating Temperature (Ta) -20° to + 55°C

Optic Specifications

LED SMD 5050 **Light Source Delivered Lumens** Up to 11,303lm **Efficacy** Up to 147lm/W **CRI** 79Ra up to 15° Adjustment Calculated L70 (Hours) >60000 Hrs Calculated L80 (Hours) >60000 Hrs

VARIATIONS


Calculated L90 (Hours)


LC6129-T1	KINGSTON 75W Streetlight, Signal Black, T1, 3000K, 9,969lm
LC6129-T2	KINGSTON 75W Streetlight, Signal Black, T2, 3000K, 9,877lm
LC6129-T3	KINGSTON 75W Streetlight, Signal Black, T3, 3000K, 10,058lm
LC6129-T4	KINGSTON 75W Streetlight, Signal Black, T4, 3000K, 10,609lm
LC6130-T1	KINGSTON 75W Streetlight, Signal Black, T1, 4000K, 10,574lm

39,000 Hrs











 LC6130-T2
 KINGSTON 75W Streetlight, Signal Black, T2, 4000K, 10,689Im

 LC6130-T3
 KINGSTON 75W Streetlight, Signal Black, T3, 4000K, 11,303Im

 LC6130-T4
 KINGSTON 75W Streetlight, Signal Black, T4, 4000K, 11,104Im

Classic Series
Proven. Quality. Customisable

