

LENNOX 72W

Asymmetric Floodlight

Classic Series

Proven. Quality. Customisable

The LENNOX 72W Linear Lens IP66 Floodlight is the premium series floodlight for professional market. Die-Cast Aluminium for enhanced Dissipation. IP66 Waterproof. Asymmetric Beam Angle, for 100% Forward Throw Light, with no back-light, reducing light pollution and glare. Enhanced corrosion resistance, using AkzoNobel Powder Coating.

Designed for external & industrial applications.



SPECIFICATIONS

Material Specifications


Material	Die-Cast Aluminium Design
Finish	AkzoNobel Powder Coat
Ingress Protection	IP66
Impact Rating	IK08
Dimensions	370 x 265 x 75mm
Weight	5.45kg
Warranty	7 Year Replacement

Electrical Specifications

Power Supply	Integrated MeanWell, Non-Dim
Input Voltage	240V; 50/60Hz
Options	DALI, 1-10V available

Optic Specifications

Light Source	Lumileds Luxeon SMD 5050
CRI	Ra 83
Colour Deviation	SDCM < 3
Calculated L70 (Hours)	154,000 Hrs
Calculated L80 (Hours)	97,000 Hrs
Calculated L90 (Hours)	46,000 Hrs



VARIATIONS

LC2520	LENNOX 72W Floodlight, Black, 90x40°, 3000K, 9,980lm
LC2522	LENNOX 72W Floodlight, Black, 90x40°, 4000K, 10,508lm
LC2524	LENNOX 72W Floodlight, Black, 90x40°, 5700K, 11,030lm