

# LINX 22W

## Linear Downlight Adjustable

The LINX 22W Linear Recessed Downlight is an ultra-miniature adjustable LED downlight. It is a perfect combination of lens & reflector. It has superior glare control. 5-module, linear light. Commercial Quality, with a 5 Year Warranty.

The secondary reflector is available in black, white, silver & gold.



### Classic Series


Proven. Quality. Customisable



## SPECIFICATIONS

### Material Specifications

Material	High Grade Aluminium
Colour	White/ Black Insert
Ingress Protection	IP40
Dimensions	309mm(L) x 70mm(W) x 60mm(D)
Cutout	298mm x 52mm
Warranty	5 Year Replacement



### Electrical Specifications

Power Supply	Actec Driver 24W, Phase Dim
Connection Method	Australian 2-Pin Plug & 1.0m Lead
Input Voltage	240V

### Optic Specifications

Light Source	Osram 22W LED COB
Delivered Lumens	1600lm-1700lm
Beam Angle	24° / 40°
CRI	90Ra
Colour Deviation	SDCM ≤ 3
UGR	<19
Reported L70 (Hours)	> 54,000 Hrs

## VARIATIONS

LC4457	LINX 22W Linear Downlight Adjustable, White, 40°, Phase Dim, 3000K, 1600lm
LC4458	LINX 22W Linear Downlight Adjustable, White, 40°, Phase Dim, 4000K, 1700lm