

LINX 7W


Linear Downlight Fixed

Classic Series

Proven. Quality. Customisable

The LINX 7W Linear Recessed Downlight is a small yet powerful LED light with superior glare control and a 3-modular design. The combination of lens and reflectors ensures efficient light distribution while minimising unwanted glare. The secondary reflector is available in four different colours: black, white, silver and gold providing customisation options to match various interior designs. Its compact size allows for easy installation in tight spaces, making it a versatile lighting solution.

Verified by Techlume Australia on 08/05/2023



IP40



SPECIFICATIONS

Material Specifications


Dimensions	96mm x 45mm (overall face)
Cutout	90mm x 37mm
Colour	White/ Black Insert
Ingress Protection	IP40
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Actec 9W Driver 700mA, Phase Dim
Connection Method	2-pin plug & 1.2m lead
Input Voltage	240V

Optic Specifications

Light Source	Osram 7W SMD
Delivered Lumens	598lm
Colour Deviation	SDCM ≤ 3
Beam Angle	24° / 40°
Reported L70 (Hours)	> 54,000 Hrs



VARIATIONS

LC4460	LINX 7W Linear Downlight, White with Black Insert, 40°, Phase Dim, 3000K, 598lm
LC4460W	LINX 7W Linear Downlight, White with White Insert, 40°, Phase Dim, 3000K, 598lm
LC4461	LINX 7W Linear Downlight, White with Black Insert, 40°, Phase Dim, 4000K, 598lm
LC4461W	LINX 7W Linear Downlight, White with White Insert, 40°, Phase Dim, 4000K, 598lm