

MICHIGAN 15W


LED Downlight

dynamic series

Efficient. Cutting Edge. Reliable

The MICHIGAN 15W downlight is dimmable, constructed with a thermal heatsink included to ensure the downlight disperses any heat keeping it cool to touch. Used by builders, developers and a favourite with electricians. The MICHIGAN Downlight is a cost effective wide beam downlight built to withstand years of use. Perfect for all purpose use in any home or commercial, including retrofits.

Verified by Techlume Australia on 02/08/2023



IP20



SPECIFICATIONS

Material Specifications

Material	High Grade Cast Aluminum + PMMA
Colour	Matt White / Matt Black
Dimensions	145mm Face Dia x 65mm (D)
Cutout	125mm (Dia)
Ingress Protection	IP20
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	TRIAC Dimmable
System Watts	13.9W
Connection Method	Australian 2-Pin Plug + 0.6m lead
Operating Temperature (Ta)	-20°C to +45°C

Optic Specifications

Light Source	Citizen LED
Delivered Lumens	1,613lm (3000K)
Delivered Lumens	1,721lm (4000K)
CRI	>84Ra
Beam Angle	60°
Rated Lifetime (L70B20)	40,000 Hrs

VARIATIONS

LC3558W	MICHIGAN 15W Downlight, White, 60°, Phase Dim, 3000K, 1,613lm
LC3558B	MICHIGAN 15W Downlight, Black, 60°, Phase Dim, 3000K, 1,613lm
LC3559W	MICHIGAN 15W Downlight, White, 60°, Phase Dim, 4000K, 1,721lm
LC3559B	MICHIGAN 15W Downlight, Black, 60°, Phase Dim, 4000K, 1,721lm

