

MILAN 36W Round 350mm Ceiling Light

Introducing the MILAN 36W Oyster Light, with powerful illumination and advanced LED technology, a modern slimline profile with a textured finish complements any residential or commercial space. Featuring a smart mounting system for ease of installation, the MILAN provides exceptional light coverage and quality light output with minimal glare.

Verified by Techlume Australia on 08/03/2023

Pressed Alumium Housing with PC Diffuser

Sandy Powder Coat

5 Year Replacement

IP20

2.2kg

HEP Driver 0.97

240V, 60Hz

350mm Dia x 65mm(H)





Classic Series

Proven. Quality. Customisable

SPECIFICATIONS

Material Specifications

Material Finish Dimensions Ingress Protection Weight Warranty

Electrical Specifications

Power Supply Power Factor Input Voltage Dimming Benefits


Optic Specifications

| Light Source | Bridgelux BXI |
|----------------------|---------------|
| Efficacy | 98lm/W |
| Delivered Lumens | 3823lm |
| Optics | Opal Diffuser |
| CRI | > 85Ra |
| Beam Angle | 107° |
| Reported L70 (Hours) | >54,000 Hrs |
| | |

Bridgelux BXEN Series LED 98lm/W 3823lm Opal Diffuser > 85Ra 107°

TRIAC Dimmable, 10%-100%

Suspension Kit available



VARIATIONS

| LC4510 | MILAN 36W Ceiling Oyster Light, White, Phase Dim, 3000K, 3563Im |
|--------|---|
| LC4511 | MILAN 36W Ceiling Oyster Light, White, Phase Dim, 4000K |
| LC4512 | MILAN 36W Ceiling Oyster Light, Black, Phase Dim, 3000K, 3563Im |
| LC4513 | MILAN 36W Ceiling Oyster Light, Black, Phase Dim, 4000K |
| LC4535 | MILAN 36W Ceiling Oyster Light, Black, Phase Dim, 3000K/4000K |
| LC4534 | MILAN 36W Ceiling Oyster Light, White, Phase Dim, 3000K/4000K |

