

MODIS-L30W

Tracklight

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.



IP20



SPECIFICATIONS

Material Specifications

Material Aluminium & Transparent Tempered Glass

Mounting Adjustable Track Mount

Colour Black RAL9005/ White RAL9016

Dimensions 85mm (Dia) x 292mm (H)

Ingress Protection IP20

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Integral Driver, 500mA, Phase Dimmable

Connection Method Terminal Block in base

Input Voltage 240V

Optic Specifications

 Light Source
 Tridonic 30W LED

 Delivered Lumens
 2550-3650lm

 CRI
 Ra >90

 Colour Deviation
 SDCM ≤ 5

 Colour Deviation
 SDCM ≤ 5

 Reported L70 (Hours)
 50,000 Hrs

VARIATIONS

LC1498B MODIS-L 30W Tracklight, Black, 36°, Phase Dim, Tri-Colour,

2550-3650lm

LC1498W MODIS-L 30W Tracklight, White, 36°, Phase Dim, Tri-Colour,

2550-3650lm





