

MODIS-L35W

Suspended Can Light

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.



IP20



SPECIFICATIONS

Material Specifications

Material Aluminium & Transparent Tempered Glass

Mounting Suspended

Ingress Protection IP20

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Integral Driver, 500mA, Phase Dimmable

Connection Method Terminal Block in base

Input Voltage 240V

Optic Specifications

Light Source Tridonic 35W LED

Correlated Colour Temperature 3-CCT: 3000K/ 4000K/ 5000K

 Delivered Lumens
 3050-4250lm

 CRI
 Ra > 90

 Colour Deviation
 SDCM ≤ 5

 Reported L70 (Hours)
 50,000 Hrs

VARIATIONS

LC1459B MODIS-L 35W Suspended Can Light, Black, 36°, Phase Dim, Tri-Colour,

3050-4250lm

LC1459W MODIS-L 35W Suspended Can Light, White, 36°, Phase Dim, Tri-Colour,

3050-4250lm





