MODIS-L 35W Suspended Can Light

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.

Suspended

IP20

240V





SPECIFICATIONS

Material Specifications

Material Mounting Colour Dimensions Ingress Protection Warranty

Electrical Specifications

Power Supply Connection Method Input Voltage 5 Year Replacement Integral Driver, 500mA, Phase Dimmable Terminal Block in base

Aluminium & Transparent Tempered Glass

Black RAL9005/ White RAL9016

100mm (Dia) x 1249mm (H)

Optic Specifications

Light Source	Tridonic 35W LED
Correlated Colour Temperature	3-CCT: 3000K/ 4000K/ 5000K
Delivered Lumens	3050-4250lm
CRI	Ra >90
Colour Deviation	SDCM ≤ 5
Reported L70 (Hours)	50,000 Hrs

VARIATIONS

LC1459B	MODIS-L 35W Suspended Can Light, Black, 36°, Phase Dim, Tri-Colour, 3050-4250Im
LC1459W	MODIS-L 35W Suspended Can Light, White, 36°, Phase Dim, Tri-Colour, 3050-4250Im



