

MODIS-M 20W

Recessed Can Light

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.



IP20





SPECIFICATIONS

Material Specifications

Material Aluminium & Transparent Tempered Glass

Mounting Recessed

Colour Black RAL9005/ White RAL9016

Dimensions 85mm (Dia) x 274mm (H)

Cutout89mmIngress ProtectionIP20

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Integral Driver, 500mA, Phase Dimmable

Connection Method Terminal Block in base

Input Voltage 240V

Optic Specifications

 Light Source
 Tridonic 20W LED

 Delivered Lumens
 1700-2650lm

 CRI
 Ra >90

 Colour Deviation
 SDCM ≤ 5

 Reported L70 (Hours)
 50,000 Hrs

0105 Ø89 Ø85

VARIATIONS

LC1476B MODIS-M 20W Recessed Can Light, Black, 36°, Phase Dim, Tri-Colour,

1700-2650lm

LC1476W MODIS-M 20W Recessed Can Light, White, 36°, Phase Dim, Tri-Colour,

1700-2650lm