

## **MODIS-S 10W**

# Tracklight

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.



**IP20** 





#### **SPECIFICATIONS**

#### **Material Specifications**

Material Aluminium & Transparent Tempered Glass

**Mounting** Adjustable Track Mount

**Colour** Black RAL9005/ White RAL9016

**Dimensions** 65mm (Dia) x 253mm (H)

Ingress Protection IP20

Warranty 5 Year Replacement

#### **Electrical Specifications**

**Power Supply** Integral Driver, 500mA, Phase Dimmable

**Connection Method** Terminal Block in base

Input Voltage 240V

#### **Optic Specifications**

**Light Source** Tridonic 10W LED


**Correlated Colour Temperature** 3-CCT: 3000K/ 4000K/ 5000K

 Delivered Lumens
 740-1200lm

 CRI
 90Ra

 Colour Deviation
 SDCM ≤ 5

 Rated Lifetime (L70B20)
 50,000 Hrs



### VARIATIONS

**LC1494B** MODIS-S 10W Tracklight, Black, 36°, Phase Dim, Tri-Colour, 740-1200lm **LC1494W** MODIS-S 10W Tracklight, White, 36°, Phase Dim, Tri-Colour, 740-1200lm