

MODIS-S 15W

Suspended Can Light

The MODIS series is a modular lighting series with an exquisite design and UGR19 anti-glare feature. It supports six installation methods, including recessed, canopy ceiling, surface-mounted, pendant, and track options. With four size choices (Ø55mm, Ø65mm, Ø85mm, Ø100mm), it uses a Bridgelux COB light source, achieving 120lm/W efficiency. It offers interchangeable CCT and wattage (except Ø55mm), multiple reflector angles, and flicker-free drivers. Ideal for commercial and residential spaces, such as hotels, offices, museums, and homes.



IP20



SPECIFICATIONS

Material Specifications

Material Aluminium & Transparent Tempered Glass

Mounting Suspended

 Colour
 Black RAL9005/ White RAL9016

 Dimensions
 65mm (Dia) x 1209mm (H)

Ingress Protection IP20

Warranty 5 Year Replacement

Electrical Specifications

Power Supply Integral Driver, 500mA, Phase Dimmable

Connection Method Terminal Block in base

Input Voltage 240V

Optic Specifications

Light SourceTridonic 15W LEDDelivered Lumens1300-1750 ImCRIRa >90Colour DeviationSDCM ≤ 5 Reported L70 (Hours)50,000 Hrs

VARIATIONS

LC1455B MODIS-S 15W Suspended Can Light, Black, 36°, Phase Dim, Tri-Colour,

1300-1750lm

LC1455W MODIS-S 15W Suspended Can Light, White, 36°, Phase Dim, Tri-Colour,

1300-1750lm





