

NEO FIREGLOW

13W Sunset Dim Downlight

Classic Series


Proven. Quality. Customisable

The NEO Fireglow Downlight Module allows the colour temperature to shift as the downlight is dimmed. This effect is called Sunset Dimming. It creates a warm 'fire glow' ambiance perfect for restaurants, hotels and cafes. It can be smoothly dimmed to a warm white (1800K).

The FIREGLOW downlight delivers 880 lumens, giving a similar appearance to the traditional dichroic lamp. As the lamp is dimmed, the colour temperature gradually becomes warmer, a replication of the behaviour of the traditional halogen lamp.



IP44



SPECIFICATIONS

Material Specifications

| | |
|---------------------------|--------------------------------|
| Material | Aluminium, with Tempered Glass |
| Dimensions | 78mm (H) x 62mm (Dia) |
| Ingress Protection | IP20 |
| Warranty | 5 Year Replacement |

Electrical Specifications

| | |
|--------------------------|---|
| Power Supply | 18W Osram OTe Driver Constant Current 260mA |
| Connection Method | Australian 2-Pin Plug & Lead |
| Input Voltage | 240V |
| Dimming | Yes |

Optic Specifications

| | |
|--------------------------------------|-------------------------------|
| Light Source | 13W Sharp LED, with Reflector |
| Beam Angle | 22° / 36° / 60° |
| Delivered Lumens | 900lm - 40lm |
| Correlated Colour Temperature | 3000K - 1800K |
| CRI | 93Ra at 3000K |
| Rated Lifetime (L70B20) | 50,000 Hrs |

VARIATIONS

| | |
|---------------|---|
| LC5160 | NEO Fireglow 13W Sunset Dim Downlight, 60°, 3000K - 1800K |
|---------------|---|

