

PONTIAC 4W


Retractable Downlight

Classic Series

Proven. Quality. Customisable

PONTIAC 4W Retractable Downlight offers great flexibility. Its miniature size makes this a minimalist lighting, while being functional and versatile. Flexible for lighting schemes in residential or retail spaces. Direct illumination with a 30° optic reflector.

Power supply is small enough to fit through hole cutout.



SPECIFICATIONS

Material Specifications


Housing	Aluminium
Finish	Powder Coat
Dimensions	54mm Face Dia
Cutout	46mm (Dia)
Adjustment	350° Rotatable, 90° Tiltable
Ingress Protection	IP20
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	6W LTECH power supply, Phase Dim
Input Voltage	240V
Connection Method	Australian Approved 2-Pin Plug & 1.0m Lead

Optic Specifications

Light Source	4W SMD LED
Delivered Lumens	420lm
Beam Angle	30°
CRI	90Ra
Reported L70 (Hours)	> 54,000 Hrs



VARIATIONS

LC4680	PONTIAC 4W Retractable Downlight, White, Phase Dim, 3000K, 414lm
LC4681	PONTIAC 4W Retractable Downlight, White, Phase Dim, 4000K, 421lm
LC4682	PONTIAC 4W Retractable Downlight, Black, Phase Dim, 3000K, 419lm
LC4683	PONTIAC 4W Retractable Downlight, Black, Phase Dim, 4000K, 434lm