

RHYNE 24W

Industrial Floodlight

Classic Series

Proven. Quality. Customisable

The 24W RHYNE LED Floodlight is a stylish slimline design, giving a wide beam spread for an even light coverage. Tempered glass with a hard-wearing, anti-corrosion finish.

Security lighting is becoming increasingly important. LED flood lights are now producing more light than ever for the illumination of domestic and commercial outdoor spaces. Huge savings can be made on power consumption over the life of the fitting. Seven year replacement warranty. Removing the plug does not affect the warranty.



IP66



SPECIFICATIONS

Material Specifications

Material	Aluminium Housing, Foggy Tempered Glass
Finish	AkzoNobel Powder Coat
Dimensions	220mm(L) x 170mm(W) x 45mm (H)
Ingress Protection	IP66
Warranty	7 Year Replacement
Weight	1.9Kg

Electrical Specifications

Power Supply	Integrated MeanWell, Non-Dim
Connection Method	Australian 2-pin Plug & 1.8m Lead
Operating Temperature (Ta)	-20°C to +50°C
Input Voltage	240V

Optic Specifications

Light Source	Edison LED, 48 pcs SMD
Beam Angle	120°
CRI	80Ra
Reported L70 (Hours)	> 54,000 Hrs
Calculated L70 (Hours)	154,000 Hrs

VARIATIONS

LC2347	RHYNE 24W Floodlight, Black, Non-Dim, 5700K, 3557lm
---------------	---

