Classic Series
Proven. Quality. Customisable

RHYNE 72W
Industrial Floodlight

The RHYNE 72W LED Floodlights are an architectural design, wide beam spread, and a hard-wearing black finish.

Great for outdoor BBQ areas, recreational spaces, security in commercial outdoor spaces. Also used in Aquatic Centres, Marine Environments, Mines, and Shipping yards. Our RHYNE floodlight series are robust, extremely dependable and offer peace of mind with our massive 7 year replacement warranty.



IP66

SPECIFICATIONS

Material Specifications


Material	Aluminium Housing, Foggy Tempered Glass
Finish	AkzoNobel Powder Coat
Dimensions	330mm(L) x 250mm(W) x 75mm (H)
Ingress Protection	IP66
Weight	4.9Kg
Warranty	7 Year Replacement

Electrical Specifications

Power Supply	Meanwell, Non-Dimmable
Connection Method	Australian 2-pin Plug & 1.8m Lead
Operating Temperature (Ta)	-20°C to +50°C
Input Voltage	240V

Optic Specifications

Light Source	Edison LED, 150 pcs SMD
Delivered Lumens	10,184lm
CRI	80Ra
Beam Angle	120°
Reported L70 (Hours)	>54,000 Hrs
Calculated L70 (Hours)	154,000 Hrs
Calculated L80 (Hours)	97,000 Hrs
Calculated L90 (Hours)	46,000 Hrs



VARIATIONS

LC2343	RHYNE 72W Floodlight, Black, 120°, Non-Dim, 5700K
LC2341D	RHYNE 72W Floodlight, Black, 120°, DALI, 3000K

Product design and technical data may be subject to change without prior notice.
Generated 28th Mar 2024 - © Decrolux

E582