decrolux Illuminating spaces. Inspiring growth.

1300 827 284 www.decrolux.com.au

RONAN 70W Exterior Wall Light

The RONAN 70W outdoor slim wall light is a durable option for upgrading traditional Slim Wall Pack light fixtures. Made with aluminium triangle extrusion and polycarbonate with a black powder coat, the light is weather-resistant and long-lasting. This light is easy to install and requires minimal maintenance, while its low-profile design makes it ideal for outdoor spaces that require lighting without being too obtrusive, and its asymmetric optic makes it dark sky friendly.

IP66

SPECIFICATIONS

Material Specifications

Material Colour Dimensions Ingress Protection Impact Rating Warranty Options

Electrical Specifications

Power Supply Operating Temperature (Ta) Input Voltage Connection Method Integral -30°C to + 45°C 240V Hard Wiring, Large Internal Cavity

Die-Cast Aluminium, Polycarbonate

282mm (L) x 125mm (D) x 205mm (H)

Black Powdercoat

5 Year Replacement

PE Cell (special orders)

IP66


IK08

Optic Specifications

Light Source	Osram LED 2835, Linear PCB
Optics	Т3
Delivered Lumens	Up to 8,750lm
Efficacy	125lm/w
CRI	> 80Ra
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs
Efficacy CRI Colour Deviation	125lm/w > 80Ra SDCM ≤ 3

VARIATIONS

LC4277	RONAN 70W Outdoor Floodlight, Black, T3, Non-Dim, 3000K, 8,140Im
LC4277D	RONAN 70W Outdoor Floodlight, Black, T3, DALI, 3000K, 8,140lm
LC4278	RONAN 70W Outdoor Floodlight, Black, T3, Non-Dim, 4000K, 8,750lm
LC4278D	RONAN 70W Outdoor Floodlight, Black, T3, DALI, 4000K, 8,750lm
LC4278-PE	RONAN 70W Outdoor Floodlight with PE Cell, Black, T3, Non-Dim, 4000K, 8,750lm





dynamic series

Efficient. Cutting Edge. Reliable



