

SORRIDI-M 25W

Adjustable Round Surface Can Light

If you think it's just another spotlight. Think again.

The SORRIDI family is the idealist's marriage of masculine and feminine characteristics into the one perfectly engineered, harmonious and ambiguous form. The **SORRIDI-M** Adjustable is perfect for creating uniformity across your project. It's smart design – exceptionally considered and minimal.



IP20



SPECIFICATIONS

Material Specifications

Material	Recycled Aluminium
Mounting	Adjustable Surface
Benefits	355° Rotation, 90° Tilt
Colour	Black / White (Both options with Black Baffle insert as standard. All white available.)
Dimensions	Ø75.6mm x 120mm (housing) Ø120mm (gear box)
Ingress Protection	IP20 (IP54 Available)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	HEP Integral Driver, 600mA, Phase-Cut Dimmable
Correlated Colour Temperature	3000K (4000K Available for Project Orders)
Options	DALI or 1-10V available
Connection Method	Terminal Block in base
Input Voltage	240V

Optic Specifications

Light Source	Tridonic 25W LED
Beam Angle	Standard 53°, 20°/33°/42° Available
Accessories	Honeycomb, Louvre (Optional Extra)
CRI	90Ra
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC1760	SORRIDI-M 25W Adjustable Surface Can Light, White, 53°, Phase Dim, 3000K, 2182lm
LC1760D	SORRIDI-M 25W Adjustable Surface Can Light, White, 53°, DALI, 3000K, 2182lm
LC1761	SORRIDI-M 25W Adjustable Surface Can Light, Black, 53°, Phase Dim, 3000K, 2270lm
LC1761D	SORRIDI-M 25W Adjustable Surface Can Light, Black, 53°, DALI, 3000K, 2270lm
LC1762	SORRIDI-M 25W Adjustable Surface Can Light, Black, 53°, Phase Dim, 4000K, 2270lm

