

1300 827 284 www.de

www.decrolux.com.au

TITAN 30W Weatherproof Batten 1220mm

The TITAN Weatherproof batten has been introduced as a premium quality batten, high-efficiency, and very easy to install. IP66, designed for harsh environments. The TITAN LED weatherproof series is an energy-efficient luminaire range that offers an efficient and effective solution for industrial environments that require protection against moisture and dust. Also available with motion sensors and emergency kits. Stainless Steel 316 Clips available.

Screws)

IK08

IP66

1.7kg

5 Year Replacement

240V 50/60Hz

-20°C to +40°C

points in rear, and 1 in side.

LG LEMWS28R80 Series

3652lm (4000K)

80Ra

120°

SDCM ≤ 3

> 54,000 Hrs

134,000 Hrs

Grey Moulded PC Body, Clear PC Diffuser

1220mm(L) x 97mm(W) x 82mm(H)

304 Stainless Clips (Supplied with 4 Anti-Tamper

Tridonic 38W Non-Dim Driver 500mA (Internal)

20mm Cable Gland at One end. 3 knock-out



SPECIFICATIONS

Material Specifications

Housing Material

Impact Rating Ingress Protection Dimensions Weight Warranty

Electrical Specifications

Power Supply Input Voltage Operating Temperature (Ta) Connection Method

Optic Specifications

Light Source Delivered Lumens CRI Beam Angle Colour Deviation Reported L70 (Hours) Calculated L70 (Hours)

VARIATIONS

| TITAN 30W Weatherproof Batten, 120°, Non-Dim, 3000K, 3505lm |
|---|
| TITAN 30W Weatherproof Batten, 120°, Non-Dim, 4000K, 3652Im |
| TITAN 30W Weatherproof Batten, 120°, Motion Sensor, 4000K, 3652lm |
| TITAN 30W Weatherproof Batten, 120°, Non-Dim, 5000K, 3750Im |
| |

dynamic series Efficient. Cutting Edge. Reliable





