

1300 827 284 www.decro

E.

www.decrolux.com.au

dynamic series

Efficient. Cutting Edge. Reliable

TITAN MK-II 50W Weatherproof Batten 1500mm

The TITAN MK-II Weatherproof batten has been introduced as a premium quality batten, high-efficiency, and very easy to install. IP65, designed for harsh environments. The TITAN LED weatherproof series is an energy-efficient luminaire range that offers an efficient and effective solution for industrial environments that require protection against moisture and dust. A versatile fitting with Tri-Colour. Available with emergency kits.

Grey Moulded PC Body, PC Diffuser, 304



SPECIFICATIONS

Material Specifications

Housing

	Stainless Steel Clips
Impact Rating	IK08
Ingress Protection	IP65
Dimensions	1500mm(L) x 125mm(W) x 88mm(H)
Weight	1.7kg
Warranty	5 Year Replacement

240V 50/60Hz

Lifud Driver, Integrated -20°C to +45°C

4-6m (mounting height 3m)

Electrical Specifications

Input Voltage Power Supply Operating Temperature (Ta) Sensor Detection Radius

Optic Specifications

Correlated Colour TemperatureTri-Colour: 3000K/ 4000K/ 5000KNominal LumensUp to 6,500lm
Efficacy Up to 130lm/W
CRI Ra>80
Calculated L70 (Hours) >170,000 Hrs
Calculated L80 (Hours) >105,000 Hrs
Calculated L90 (Hours) >51,000 Hrs

VARIATIONS

LC5367	TITAN MK-II 50W Weatherproof Batten, 1500mm, 120°, Non-Dim, Tri- Colour
LC5367-MS	TITAN MK-II 50W Weatherproof Batten, 1500mm, 120°, w. Motion Sensor, Tri-Colour
LC5367-EM	TITAN MK-II 50W Weatherproof Emergency Batten, 1500mm, 120°, Tri- Colour
LC5367- EM-MS	TITAN MK-II 50W Weatherproof Emergency Batten, 1500mm, 120°, w. Motion Sensor, Tri-Colour
LC5367D	TITAN MK-II 50W Weatherproof Batten, 1500mm, 120°, DALI, Tri-Colour





