

dynamic series



Efficient. Cutting Edge. Reliable

TITAN MK-II 20W

Weatherproof Batten 600mm

The TITAN MK-II Weatherproof batten has been introduced as a premium quality batten, high-efficiency, and very easy to install. IP65, designed for harsh environments. The TITAN LED weatherproof series is an energy-efficient luminaire range that offers an efficient and effective solution for industrial environments that require protection against moisture and dust. A versatile fitting with Tri-Colour, and 3 wattage selections.

Also available with motion sensors and emergency kits.



SPECIFICATIONS

Material Specifications

Housing	Grey Moulded PC Body, Clear PC Diffuser
Material	304 Stainless Clips
Impact Rating	IK08
Ingress Protection	IP65
Dimensions	600mm(L) x 83mm(W) x 72mm(H)
Weight	1.42kg
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Integrated Lifud Driver
System Watts	20W
Input Voltage	240V 50/60Hz
Operating Temperature (Ta)	-20°C to +45°C
Connection Method	20mm Cable Gland at One end. 3 knock-out points in rear, and 1 in side.

Optic Specifications

Light Source	Epistar SMD2835
Correlated Colour Temperature	3000K/ 4000K/ 5000K
Delivered Lumens	2600lm - 3900lm
CRI	80Ra
Colour Deviation	SDCM ≤ 3
Reported L70 (Hours)	> 54,000 Hrs
Calculated L70 (Hours)	134,000 Hrs

VARIATIONS

LC5362	TITAN MK-II 20W Weatherproof Batten, 120°, Non-Dim, Tri-Colour
LC5362-MS	TITAN MK-II 20W Weatherproof Batten, 120°, Motion Sensor, Tri-Colour
LC5362D	TITAN MK-II 20W Weatherproof Batten, 120°, DALI, Tri-Colour