

VENUS 200W

Industrial Highbay

Classic Series

Proven. Quality. Customisable

The VENUS 200W Highbay is a compact design with a slim housing. With an IP66 rating, it is corrosion resistant and suitable for outdoor and wet applications. This model has increased efficiency and lumen output with an improved heat sink, ensuring a long-lasting maintenance-free life.

Impact Rating of IK08 with standard glass cover. With optional Polycarbonate cover, IK10 is available.

Verified by Techlume Australia on 15/08/2023



SPECIFICATIONS

Material Specifications

Material	Die-Cast Aluminium
Finish	Anti-Corrosion AkzoNobel Powdercoat
Dimensions	380mm Dia x 230mm(H)
Mounting	U-Bracket (Hook and chain not supplied)
Impact Rating	IK08
Ingress Protection	IP66
Weight	5.68kg
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	Meanwell Integrated, Non-Dimmable, 5000mA
System Watts	213.4W - 216.7W
Dimming	Dali, 0-10V Available
Operating Temperature (Ta)	-20°C to +50°C
Connection Method	2m double-insulated 3-core flex with 3-pin plug

Optic Specifications

Light Source	288 x Lumileds Luxeon 3030
Delivered Lumens	30,223lm (3000K)
Delivered Lumens	30,284lm (4000K)
Delivered Lumens	34,360lm (5700K)
Efficacy	Up to 158.5lm/W
CRI	Ra >71
Beam Angle	120° / 60°
Calculated L70 (Hours)	115,000 Hrs



VARIATIONS

LC2406	VENUS 200W Highbay, Black, 120°, Non-Dim, 3000K, 30,223lm
LC2407	VENUS 200W Highbay, Black, 120°, Non-Dim, 4000K, 30,284lm
LC2408	VENUS 200W Highbay, Black, 120°, Non-Dim, 5700K, 34,360lm