

VERTEX MK-II 1350W

1350W Industrial Floodlight

Classic Series

Proven. Quality. Customisable

The VERTEX Floodlights are designed for flexibility in high output situations. The VERTEX MK-II 1350W Industrial Floodlight is suitable for mounting heights of up to 30 metres. The robust construction with a high lumen output enables optimum light spread for high light requirements. The updated design is more compact, for less wind force, and an improved bracket design.



IP66



SPECIFICATIONS

Material Specifications

Material	Die-Cast Aluminium Housing
Finish	AkzoNobel Powder Coat
Dimensions	628mm (W) x 910mm (H) x 275mm (D)
Windage	0.140m ² at 20° tilt
Maximum Projected Area	0.481m ²
Ingress Protection	IP66
Impact Rating	IK10
Weight	44.3 kg (including drivers)
Weight	26.2kg (without drivers)
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	4 x Meanwell HLG-320 Drivers
Input Voltage	240V (5 amps)
Max Distance From Power Supply	50m
Connection Method	Drivers can be remoted mounted

Optic Specifications

Light Source	1350W Lumileds Luxeon
Calculated L70 (Hours)	155,000 Hrs
Calculated L80 (Hours)	97,000 Hrs
Calculated L90 (Hours)	46,000 Hrs

VARIATIONS

LC6473	VERTEX 1350W Floodlight, Black, 15°, Non-Dim, 5700K, 172,600lm
LC6474	VERTEX 1350W Floodlight, Black, 25°, Non-Dim, 5700K, 206,800lm
LC6475	VERTEX 1350W Floodlight, Black, 60°, Non-Dim, 5700K, 206,800lm
LC6476	VERTEX 1350W Floodlight, Black, 110°, Non-Dim, 5700K, 210,700lm

