
1300 827 284

Z21-BATT 36W

Explosion Proof Emergency Batten

The Z21-BATT 36W Explosion-Proof Batten, is a meticulously designed system that sets the standard for peak performance and durability in hazardous environments. Along with its explosion-proof features, it includes an anti-glare design for focused and evenly distributed light, ensuring optimal visibility. Specially treated powder-coated paintwork enhances the fixture's aesthetics while rendering it salt, chemical-resistant, and resistant to dust accumulation, minimising maintenance needs. Crafted with precision from top-tier materials like ADC12 alloy, one-piece neoprene gaskets, 6063 aluminum, and a polycarbonate lens. Versatile mounting options are available, meaning the Z21 Batten is suitable across diverse hazardous settings.







EXPLOSION PROOF

SPECIFICATIONS

Material Specifications

Material 6063 Aluminium Housing with Polycarbonate

Lens

Finish Yellow Powdercoat

Application Surface Mounted - Ceiling/ Wall **Mounting** Stainless Steel Brackets

Dimensions 1285mm(L) x 126mm(W) x 88mm(D)

 Weight
 7.5 Kg

 Impact Rating
 IK10

 Ingress Protection
 IP66

Warranty 5 Year Replacement

Electrical Specifications

System Watts 45W (Maintained), 15W (Non-Maintained) **Mode of Operation** Multimode - Maintained/ Non-Maintained

Battery & Charger System Ni-MH (Built-in) **Operating Temperature (Ta)** $-40^{\circ}\text{C to }50^{\circ}\text{C}$

Protection Overcharge, Low Voltage Disconnect,

overcurrent, short circuit

Emergency Duration 90 Minutes

Testing FacilityManual Test SwitchIndicatorsBattery Charger Green LED

Optic Specifications

LED Wattage 36W LED (15W Emergency)

AS2293 Classification C0-D80, C90-D50

 Efficacy
 130lm/W

 Delivered Lumens
 4680lm

 Reported L70 (Hours)
 > 50,000 Hrs

VARIATIONS

Z21-BATT1236-EM Z21-BATT 36W Explosion Proof Emergency Batten, Yellow, 5000K,

1680IM

