

ZORIN 50W

Premium Floodlight

Classic Series

Proven. Quality. Customisable

The ZORIN LED Floodlight range is built to perform in demanding outdoor environments. Featuring robust die-cast aluminium construction with corrosion-resistant powder coating, it delivers reliable, long-lasting operation with minimal maintenance. The precision-adjustable bracket allows flexible installation and easy aiming to suit a wide range of applications. With a high-efficiency LED light source and multiple beam angle options, the ZORIN Floodlight provides powerful, uniform illumination wherever it's needed. Available in a variety of wattages and dimming options, and backed by a 7-year warranty, it's a dependable choice for commercial and industrial lighting projects.



SPECIFICATIONS

Material Specifications



Housing	Aluminium Die-casting Body, with SS316 screws, Tempered Glass Lens
Finish	AkzoNobel Powder Coat, Black or Grey
Benefits	Corrosion Resistant, Smooth Self-Cleaning Housing
Dimensions	295mm(L) x 218mm(W) x 51mm(H)
Ingress Protection	IP66
Impact Rating	IK08
Weight	2.6kg
Warranty	7 Year Replacement

Electrical Specifications

Power Supply	Isolated Flicker-Free Driver
Dimming	Non-Dim (Standard), DALI-2 or 0-10V Available
Input Voltage	240V
Power Factor	>0.95
Operating Temperature (Ta)	-20°C to +50°C
Protection	6KV Surge Protection

Optic Specifications

Light Source	5050 SMD LED Chips
Delivered Lumens	8,000lm (4000K)
Efficacy	Up to 160lm/W
CRI	>70



VARIATIONS

ZRN050-4K-90-B	ZORIN 50W Floodlight, Black, 90°, Non-Dim, 4000K
ZRN050-4K-90-G	ZORIN 50W Floodlight, Grey, 90°, Non-Dim, 4000K
ZRN050-4K-100x60-B	ZORIN 50W Floodlight, Black, 100x60°, Non-Dim, 4000K