

ZORIN 75W

Premium Floodlight

Classic Series

Proven. Quality. Customisable

The ZORIN LED Floodlight range is built to perform in demanding outdoor environments. Featuring robust die-cast aluminium construction with corrosion-resistant powder coating, it delivers reliable, long-lasting operation with minimal maintenance. The precision-adjustable bracket allows for flexible installation and easy aiming, making it suitable for a wide range of applications. With multiple beam angle options, the ZORIN Floodlight provides powerful, uniform illumination wherever it's needed. Available in a variety of wattages and backed by a 7-year warranty, it's a dependable choice for commercial and industrial lighting projects.



SPECIFICATIONS

Material Specifications

Housing	Aluminium Die-casting Body, with SS316 screws, Tempered Glass Lens
Finish	AkzoNobel Powder Coat, Black or Grey
Benefits	Corrosion Resistant, Smooth Self-Cleaning Housing
Dimensions	379mm(L) x 278mm(W) x 55mm (H)
Ingress Protection	IP66
Impact Rating	IK08
Weight	4.1Kg
Warranty	7 Year Replacement

Electrical Specifications

Input Voltage	240V
Power Supply	Isolated Flicker-Free Driver
Dimming	Non-Dim (Standard), DALI-2 Available
Operating Temperature (Ta)	-20°C to +50°C
Protection	10KV Surge Protection

Optic Specifications

Light Source	5050 SMD LED Chips
Delivered Lumens	12,500lm (4000K)
Efficacy	Up to 160lm/W
CRI	>70

VARIATIONS

ZRN075-4K-90-B	ZORIN 75W Floodlight, Black, 90°, Non-Dim, 4000K
ZRN075-4K-90-W	ZORIN 75W Floodlight, White, 90°, Non-Dim, 4000K
ZRN075-4K-100x60-B	ZORIN 75W Floodlight, Black, 100x60°, Non-Dim, 4000K

